

AP® Physics C: Electricity and Magnetism 2005 Free-Response Questions

The College Board: Connecting Students to College Success

The College Board is a not-for-profit membership association whose mission is to connect students to college success and opportunity. Founded in 1900, the association is composed of more than 4,700 schools, colleges, universities, and other educational organizations. Each year, the College Board serves over three and a half million students and their parents, 23,000 high schools, and 3,500 colleges through major programs and services in college admissions, guidance, assessment, financial aid, enrollment, and teaching and learning. Among its best-known programs are the SAT $^{\text{(B)}}$, the PSAT/NMSQT $^{\text{(B)}}$, and the Advanced Placement Program $^{\text{(B)}}$ (AP $^{\text{(B)}}$). The College Board is committed to the principles of excellence and equity, and that commitment is embodied in all of its programs, services, activities, and concerns.

Copyright © 2005 by College Board. All rights reserved. College Board, AP Central, APCD, Advanced Placement Program, AP, AP Vertical Teams, Pre-AP, SAT, and the acorn logo are registered trademarks of the College Entrance Examination Board. Admitted Class Evaluation Service, CollegeEd, Connect to college success, MyRoad, SAT Professional Development, SAT Readiness Program, and Setting the Cornerstones are trademarks owned by the College Entrance Examination Board. PSAT/NMSQT is a registered trademark of the College Entrance Examination Board and National Merit Scholarship Corporation. Other products and services may be trademarks of their respective owners. Permission to use copyrighted College Board materials may be requested online at: http://www.collegeboard.com/inquiry/cbpermit.html.

Visit the College Board on the Web: www.collegeboard.com.

AP Central is the official online home for the AP Program and Pre-AP: apcentral.collegeboard.com.

TABLE OF INFORMATION FOR 2005

CONSTANTS AND CONVERSION FACTORS		UNITS		PREFIXES			
	$1 \text{ u} = 1.66 \times 10^{-27} \text{ kg}$	<u>Name</u>	Symbol	Factor	<u>Prefi</u>	x Sym	<u>ıbol</u>
1 unified atomic mass unit,		meter	m	10 ⁹	giga	G	
	= 931 MeV/ c^2	kilogram	kg	10 ⁶	mega	ı M	
Proton mass,	$m_p = 1.67 \times 10^{-27} \text{ kg}$	second	s	10 ³	kilo		
Neutron mass,	$m_n = 1.67 \times 10^{-27} \text{ kg}$						
Electron mass,	$m_e = 9.11 \times 10^{-31} \mathrm{kg}$	ampere	A	10^{-2}	centi	c	
Magnitude of the electron charge,	$e = 1.60 \times 10^{-19} \mathrm{C}$	kelvin	K	10^{-3}	milli	m	
Avogadro's number,	$N_0 = 6.02 \times 10^{23} \mathrm{mol}^{-1}$	mole	mol	10^{-6}	micro	ρ μ	
Universal gas constant,	$R = 8.31 \text{ J/} (\text{mol} \cdot \text{K})$	hertz	Hz	10^{-9}	nano	n	
Boltzmann's constant,	$k_B = 1.38 \times 10^{-23} \text{J/K}$	newton	N	10^{-12}	pico	р	
Speed of light,	$c = 3.00 \times 10^8 \mathrm{m/s}$	pascal	Pa	10	pieo	Р	
Planck's constant,	$h = 6.63 \times 10^{-34} \mathrm{J \cdot s}$	puscur	1 4	VALUES OF TRIGONOMETRIC FUNCTIONS FOR COMMON ANGLE		-	
	$= 4.14 \times 10^{-15} \mathrm{eV} \cdot \mathrm{s}$	joule	J				
	$hc = 1.99 \times 10^{-25} \mathrm{J \cdot m}$	watt	W	θ	sin θ	cos θ	tan θ
	$= 1.24 \times 10^3 \text{eV} \cdot \text{nm}$	coulomb	C	0°	0	1	0
Vacuum permittivity,	$\epsilon_0 = 8.85 \times 10^{-12} \mathrm{C}^2 /\mathrm{N} \cdot \mathrm{m}^2$	volt	V	30°	1./2	$\sqrt{3}/2$	$\sqrt{3}/3$
Coulomb's law constant,	$k = 1/4\pi\epsilon_0 = 9.0 \times 10^9 \mathrm{N} \cdot \mathrm{m}^2/\mathrm{C}^2$	ohm	Ω	30	1/2	√ 312	√3/3
Vacuum permeability,	$\mu_0 = 4\pi \times 10^{-7} (\mathrm{T \cdot m}) / \mathrm{A}$	henry	Н	37°	3/5	4/5	3/4
Magnetic constant,	$k' = \mu_0 / 4\pi = 10^{-7} (\text{T} \cdot \text{m}) / \text{A}$	farad	F		_		
Universal gravitational constant,	$G = 6.67 \times 10^{-11} \text{ m}^3/\text{kg s}^2$	tesla	T	45°	$\sqrt{2}/2$	$\sqrt{2}/2$	1
Acceleration due to gravity	0 0.07 × 10 m / kg 3	degree	°C	53°	1.15	2.15	412
at the Earth's surface,	$g = 9.8 \mathrm{m/s^2}$	Celsius	C		4/5	3/5	4/3
1 atmosphere pressure,	$1 \text{ atm} = 1.0 \times 10^5 \text{ N/m}^2$	electron- volt	eV	60°	$\sqrt{3}/2$	1/2	$\sqrt{3}$
	$= 1.0 \times 10^5 \mathrm{Pa}$						·
1 electron volt,	$1 \text{ eV} = 1.60 \times 10^{-19} \text{ J}$			90°	1	0	∞
		<u> </u>			•		

The following conventions are used in this examination.

- I. Unless otherwise stated, the frame of reference of any problem is assumed to be inertial.
- II. The direction of any electric current is the direction of flow of positive charge (conventional current).
- III. For any isolated electric charge, the electric potential is defined as zero at an infinite distance from the charge.

ADVANCED PLACEMENT PHYSICS C EQUATIONS FOR 2004 and 2005

MECHANICS

υ	=	v_0	+	at	
					1

$$x = x_0 + v_0 t + \frac{1}{2} a t^2$$

$$v^2 = {v_0}^2 + 2a(x - x_0)$$

$$\sum \mathbf{F} = \mathbf{F}_{net} = m\mathbf{a}$$

$$\mathbf{F} = \frac{d\mathbf{p}}{dt}$$

$$\mathbf{J} = \int \mathbf{F} \, dt = \Delta \mathbf{p}$$

$$\mathbf{p} = m\mathbf{v}$$

$$F_{fric} \le \mu N$$

$$W = \int \mathbf{F} \cdot d\mathbf{r}$$

$$K = \frac{1}{2}mv^2$$

$$P = \frac{dW}{dt}$$

$$P = \mathbf{F} \cdot \mathbf{v}$$

$$\Delta U_g \ = mgh$$

$$a_c = \frac{v^2}{r} = \omega^2 r$$

$$\tau = \mathbf{r} \times \mathbf{F}$$

$$\sum \mathbf{\tau} = \mathbf{\tau}_{net} = I\mathbf{\alpha}$$

$$I = \int r^2 dm = \sum mr^2$$

$$\mathbf{r}_{cm} = \sum m\mathbf{r}/\sum m$$

$$v = r\omega$$

$$\mathbf{L} = \mathbf{r} \times \mathbf{p} = I\mathbf{\omega}$$

$$K = \frac{1}{2}I\omega^2$$

$$\omega = \omega_0 + \alpha t$$

$$\theta = \theta_0 + \omega_0 t + \frac{1}{2} \alpha t^2$$

$$\mathbf{F}_{\mathbf{s}} = -k\mathbf{x}$$

$$U_s = \frac{1}{2}kx^2$$

$$T = \frac{2\pi}{\omega} = \frac{1}{f}$$

$$T_s = 2\pi \sqrt{\frac{m}{k}}$$

$$T_p = 2\pi \sqrt{\frac{\ell}{\varrho}}$$

$$\mathbf{F}_G = -\frac{Gm_1m_2}{r^2}\,\hat{\mathbf{r}}$$

$$U_G = -\frac{Gm_1m_2}{r}$$

a = acceleration

F = force

f = frequency

h = height

I = rotational inertia

J = impulse

K = kinetic energy

k = spring constant

 $\ell = length$

L = angular momentum

m = mass

N = normal force

P = power

p = momentum

r = radius or distance

 \mathbf{r} = position vector

T = period

t = time

U = potential energy

v = velocity or speed C = -

W =work done on a system

x = position

 μ = coefficient of friction

 θ = angle τ = torque

 τ = torque

 ω = angular speed

 α = angular acceleration

ELECTRICITY AND MAGNETISM

$$F = \frac{1}{4\pi\epsilon_0} \frac{q_1 q_2}{r^2}$$

$$\mathbf{E} = \frac{\mathbf{F}}{a}$$

$$\oint \mathbf{E} \cdot d\mathbf{A} = \frac{Q}{\epsilon_0}$$

$$E = -\frac{dV}{dr}$$

$$V = \frac{1}{4\pi\epsilon_0} \sum_{i} \frac{q_i}{r_i}$$

$$U_E = qV = \frac{1}{4\pi\epsilon_0} \frac{q_1 q_2}{r}$$

$$C = \frac{Q}{V}$$

$$C = \frac{\kappa \epsilon_0 A}{d}$$

$$C_p = \sum_i C_i$$

$$\frac{1}{C_s} = \sum_{i} \frac{1}{C_i}$$

$$I = \frac{dQ}{dt}$$

$$U_c = \frac{1}{2}QV = \frac{1}{2}CV^2$$

$$R = \frac{\rho \ell}{A}$$

$$V = IR$$

$$R_s = \sum_i R_i$$

$$\frac{1}{R_p} = \sum_{i} \frac{1}{R_i}$$

$$P = IV$$

$$\mathbf{F}_{\scriptscriptstyle M} = q\mathbf{v} \times \mathbf{B}$$

$$\oint \mathbf{B} \cdot d\mathbf{\ell} = \mu_0 I$$

$$\mathbf{F} = \int I \, d\boldsymbol{\ell} \times \mathbf{B}$$

$$B_s = \mu_0 nI$$

$$\phi_m = \int \mathbf{B} \cdot d\mathbf{A}$$

$$\varepsilon = -\frac{d\phi_{m}}{dt}$$

$$\varepsilon = -L \frac{dI}{dt}$$

$$U_L = \frac{1}{2}LI^2$$

A = area

A = areaB = magnetic field

C = capacitance

d = distance

E = electric field

 $\varepsilon = \text{emf}$

F = force

I = current

L = inductance

 $\ell = length$

n = number of loops of wire
per unit length

P = power

Q = charge

q = point charge

R = resistance

r = distance

t = time

U =potential or stored energy

V = electric potential

v = velocity or speed

 ρ = resistivity

 ϕ_m = magnetic flux

 κ = dielectric constant

ADVANCED PLACEMENT PHYSICS C EQUATIONS FOR 2004 and 2005

GEOMETRY AND TRIGONOMETRY

Rectangle
$$A = area$$

 $A = bh$ $C = circumference$

Triangle
$$V = \text{volume}$$

$$A = \frac{1}{2}bh$$
 $S = \text{surface area}$
 $b = \text{base}$

Circle
$$h = \text{height}$$

 $A = \pi r^2$ $\ell = \text{length}$

$$C = 2\pi r$$
 $w =$ width Parallelepiped $r =$ radius

$$V = \ell wh$$

Cylinder

$$V = \pi r^2 \ell$$

$$S = 2\pi r\ell + 2\pi r^2$$

Sphere

$$V = \frac{4}{3} \pi r^3$$

$$S = 4\pi r^2$$

Right Triangle

$$a^2 + b^2 = c^2$$

$$\sin\theta = \frac{a}{c}$$

$$\cos\theta = \frac{b}{c}$$

$$\tan\theta = \frac{a}{b}$$

CALCULUS

$$\frac{df}{dx} = \frac{df}{du}\frac{du}{dx}$$

$$\frac{d}{dx}(x^n) = nx^{n-1}$$

$$\frac{d}{dx}(e^x) = e^x$$

$$\frac{d}{dx}(\ln x) = \frac{1}{x}$$

$$\frac{d}{dx}(\sin x) = \cos x$$

$$\frac{d}{dx}(\cos x) = -\sin x$$

$$\int x^n dx = \frac{1}{n+1} x^{n+1}, n \neq -1$$

$$\int e^x dx = e^x$$

$$\int \frac{dx}{x} = \ln|x|$$


$$\int \cos x \, dx = \sin x$$

$$\int \sin x \, dx = -\cos x$$

PHYSICS C

Section II, ELECTRICITY AND MAGNETISM Time—45 minutes 3 Questions


Directions: Answer all three questions. The suggested time is about 15 minutes for answering each of the questions, which are worth 15 points each. The parts within a question may not have equal weight. Show all your work in the pink booklet in the spaces provided after each part, NOT in this green insert.



E&M. 1.

Consider the electric field diagram above.


- (a) Points A, B, and C are all located at y = 0.06 m.
 - i. At which of these three points is the magnitude of the electric field the greatest? Justify your answer.
 - ii. At which of these three points is the electric potential the greatest? Justify your answer.
- (b) An electron is released from rest at point B.
 - i. Qualitatively describe the electron's motion in terms of direction, speed, and acceleration.
 - ii. Calculate the electron's speed after it has moved through a potential difference of 10 V.
- (c) Points *B* and *C* are separated by a potential difference of 20 V. Estimate the magnitude of the electric field midway between them and state any assumptions that you make.
- (d) On the diagram, draw an equipotential line that passes through point *D* and intersects at least three electric field lines.



E&M. 2.


In the circuit shown above, resistors 1 and 2 of resistance R_1 and R_2 , respectively, and an inductor of inductance L are connected to a battery of emf \mathcal{E} and a switch S. The switch is closed at time t=0. Express all algebraic answers in terms of the given quantities and fundamental constants.

- (a) Determine the current through resistor 1 immediately after the switch is closed.
- (b) Determine the magnitude of the initial rate of change of current, dI/dt, in the inductor.
- (c) Determine the current through the battery a long time after the switch has been closed.
- (d) On the axes below, sketch a graph of the current through the battery as a function of time.



Some time after steady state has been reached, the switch is opened.

(e) Determine the voltage across resistor 2 just after the switch has been opened.



E&M. 3.


A student performs an experiment to measure the magnetic field along the axis of the long, 100-turn solenoid PQ shown above. She connects ends P and Q of the solenoid to a variable power supply and an ammeter as shown. End P of the solenoid is taped at the 0 cm mark of a meterstick. The solenoid can be stretched so that the position of end Q can be varied. The student then positions a Hall probe* in the center of the solenoid to measure the magnetic field along its axis. She measures the field for a fixed current of 3.0 A and various positions of the end Q. The data she obtains are shown below.

Trial	Position of End Q (cm)	Measured Magnetic Field (T) (directed from <i>P</i> to <i>Q</i>)	n (turns/m)
1	40	9.70×10^{-4}	
2	50	7.70×10^{-4}	
3	60	6.80×10^{-4}	
4	80	4.90×10^{-4}	
5	100	4.00×10^{-4}	

⁽a) Complete the last column of the table above by calculating the number of turns per meter.

^{*}A Hall Probe is a device used to measure the magnetic field at a point.

(b) On the axes below, plot the measured magnetic field B versus n. Draw a best-fit straight line for the data points.



- (c) From the graph, obtain the value of μ_0 , the magnetic permeability of vacuum.
- (d) Using the theoretical value of $\mu_0 = 4\pi \times 10^{-7} \ (\text{T-m})/\text{A}$, determine the percent error in the experimental value of μ_0 computed in part (c).

END OF SECTION II, ELECTRICITY AND MAGNETISM